

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/045685 A1

(51) International Patent Classification⁷: A61M 5/32, 5/50

✓ (21) International Application Number:
PCT/IT2002/000730

✓ (22) International Filing Date:
18 November 2002 (18.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicants and

✓ (72) Inventors: **RESTELLI**, Sergio [IT/IT]; Via Quarto
Peperino, 333 B, I-00100 Roma (IT). **RIGHI**, Nardino
[IT/IT]; Via Cavour, 7, I-20047 Brugherio (IT). **ROSSI**,
Roberto [IT/IT]; Via delle Ande, 10, I-20151 Milano (IT).

(74) Agents: **PETRUZZIELLO**, Aldo et al.; Racheli & C. srl,
Viale San Michele del Carso, 4, I-20144 Milano (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: GUARD MECHANISM ATTACHABLE TO STANDARD SYRINGE TO TRANSFORM IT INTO A SAFETY SYRINGE



(57) Abstract: In a syringe (100) comprising a syringe body (1) hollow on the inside, a plunger (4) slidable in the syringe body (1) and provided at the rear with a shaft (41) that can be operated manually, an injection needle (2) engageable to the front end (13) of the syringe body (1) by means of a needle-carrier (20), there is attached a guard mechanism (200) comprising a sleeve (5), a spring (7) and an abutment member (8) for the spring. The abutment member (8) is mounted in the head of the syringe and the spring (7) is disposed between the sleeve (5) and the abutment member (8). The sleeve (5) can pass from a retracted position of use, wherein the needle (2) protrudes forward therefrom to a forward position of safety, wherein it covers the needle.

WO 2004/045685 A1

GUARD MECHANISM ATTACHABLE TO STANDARD SYRINGE TO TRANSFORM IT INTO A SAFETY SYRINGE

DESCRIPTION

The present invention refers to a guard mechanism attachable to a conventional syringe to make it into a disposable automatic safety syringe. The present invention also refers to a disposable automatic safety syringe obtained with said guard mechanism.

5 As is known, a syringe generally comprises a cylindrical body open at the rear to receive a plunger. A needle hollow on the inside is mounted at the head of the syringe body. On retraction of the plunger the liquid contained in a vial is drawn into the syringe body through the needle. On pressing on the plunger the liquid contained in the syringe body is injected, through the needle, into the patient's body.

10

Because of health regulations and to avoid transmission of infectious diseases, syringes must generally be used only once and then discarded. For this reason, there is a growing market demand for disposable syringes able to prevent further use.

15 Moreover, syringes generally present drawbacks from the point of view of safety. In fact, once the syringe has been used, the needle remains exposed at the head of the syringe body, with the risk of injuries and accidental needle sticks.

20 Patent application PCT WO 99/37345 describes a disposable safety syringe which has a needle covering sleeve mounted axially on the body of the syringe and slidable from a retracted position, wherein it leaves the needle exposed to allow injection, to a forward position wherein it completely covers the needle, preventing re-use of the syringe and acting as a guard against accidental needle sticks.

25 Once the injection has been performed, the sleeve is automatically brought into the extracted safety position, by means of an automatic mechanism and without any intervention by the user. However, this solution presents a certain complexity due to the presence of various additional elements for operation of the automatic mechanism.

The object of the present invention is to eliminate the drawbacks of the prior art, providing a guard mechanism that is extremely versatile and suitable to be applied to a conventional syringe to make it into a disposable automatic safety syringe.

- 5 Another object of the present invention is to provide such a guard mechanism that is economical, simple to make and simple to assemble.

Another object of the invention is to provide such a mechanism that allows a controlled intervention of the guard on the syringe on completion of the injection.

10

Yet another object of the present invention is to provide such a disposable automatic safety syringe that is able to prevent both further attempts at use of the needle and accidental injury after use thereof.

- 15 These objects are achieved in accordance with the invention with the guard mechanism according to appended independent claim 1 and with the disposable automatic safety syringe according to appended independent claim 12.

Advantageous embodiments of the invention are apparent from the dependent claims.

20

According to the invention a guard mechanism is applied to a standard syringe to make it into a disposable automatic safety syringe.

- 25 The syringe comprises a syringe body hollow on the inside and open at the front and the rear, a plunger that can slide inside the syringe body with an injection stroke extending from a retracted syringe-filling position to a forward syringe-emptying position, and an injection needle supported by a needle-carrying support engageable to the fore end of the syringe body. The plunger is provided at the rear with a shaft that can be operated manually and brought out of the syringe body through the rear end thereof.

30

The guard mechanism comprises a sleeve, spring means and an abutment member for the spring.

- 35 The abutment member for the spring is suitable to be mounted at the head of the syringe body and can act as a support for a injection needle.

The sleeve is mounted so that it can slide over the spring abutment member and the syringe body, to pass from a retracted position of use of the syringe to a forward position of safety, wherein it covers the needle.

- 5 The spring means are disposed under compression in the front part of the sleeve between the sleeve and the abutment member to urge the axial movement of the sleeve in the forward position of safety with respect to the syringe body.

- 10 The sleeve is locked in the position of use of the syringe by means of locking means, in reciprocal engagement, provided in the rear part of the sleeve and of the syringe body.

- 15 In the rear part of the shaft, on the other hand, operating means are provided to release the locking means when the plunger reaches the end of the injection stroke, so as to allow the action of the spring means which automatically generate the axial movement of the sleeve with respect to the syringe body. Such operating means can be made integral with the shaft, or they can form part of the guard mechanism and thus can be applied to the shaft.

- 20 The advantages of the guard mechanism according to the invention are evident.

- 25 In fact such a guard mechanism, comprising only three additional elements, that is to say the sleeve, the spring means, and the spring abutment means, proves extremely cheap and simple to make, and can be applied in a simple and convenient manner to a conventional syringe either automatically or manually to make it into a disposable automatic safety syringe.

The disposable automatic safety syringe obtained with a guard mechanism according to the invention is practical for the user and meets the objects of the present invention.

- 30 In fact, once the injection has been completed, the sleeve automatically and without any intervention by the user moves telescopically on the syringe body, so as to cover the needle. In this manner the needle comes to be in a position of safety, thus avoiding accidental needle sticks and possible attempts to reuse the needle, which remains trapped in the sleeve.

Further characteristics of the invention will be made clearer by the detailed description that follows, referring to a purely exemplary and therefore non limiting embodiment thereof, illustrated in the appended drawings, wherein:

- 5 Figure 1 is an exploded axonometric view, illustrating the guard mechanism according to the invention and a conventional syringe;

Figure 2 is an axial sectional view of a sleeve forming part of the guard mechanism of Figure 1;

10

Figure 3 is an axial sectional view of a spring abutment member forming part of the guard mechanism of Figure 1;

15

Figure 4 is a view, partially in axial section, of the syringe of Figure 1 assembled with the guard mechanism, wherein the shaft of the plunger has not been sectioned and has a safety tab and the needle is shown partially broken off;

20

Figure 5 is an axial sectional view, like Figure 4, of the syringe assembled with the guard mechanism, wherein the safety tab of the plunger shaft has been removed and the plunger is at its forward end-of-stroke point;

25

Figure 6 is an axial sectional view, like Figure 4, of the syringe assembled with the guard mechanism, wherein the needle is in the safety position protected by the sleeve and wherein the syringe body and plunger shaft assembly is shown partially broken off;

30

Figure 7 is an axonometric view of the syringe assembled with the guard mechanism, during use; and

Figure 8 is an axonometric view of the syringe assembled with the guard mechanism in the safety position.

The guard mechanism according to the invention, attachable to a syringe to make it into a disposable automatic safety syringe, is described with the aid of the figures.

WO 2004/045685

With reference for now in particular to Figure 1, there is illustrated a conventional syringe, denoted as a whole with reference numeral 100, and guard mechanism consisting of a set of components, denoted as a whole by reference numeral 200.

- 5 The syringe 100 is a syringe commonly available on the market and comprises a syringe body 1, an injection needle 2, a plunger 4 and a shaft 41.

- 10 The syringe body 1 is cylindrical, hollow on the inside, and defines a cylindrical chamber 10. The rear end of the body 1 is outwardly open and has an annular collar 11 that protrudes radially outward. Two tongues or flanges (not shown) that protrude radially outward, in diametrically opposite positions, can be provided on the annular rim 11 to define gripping means for the user's fingers.

- 15 The front end of the body 1 ends in a head 115, outwardly open, having the shape of a substantially cylindrical or frusto-conical tang, with a much smaller diameter than the body 1, so as to define a shoulder 15 on the front part of the syringe body 1.

- 20 The injection needle 2 is mounted on or built-in in a cylindrical or frusto-conical needle-carrier 20, hollow on the inside, having an axial chamber 23 able to receive the tang 115 of the head of the syringe body. The needle-carrier 20 can have, at its free end, a collar 21 with two tongues 22 protruding radially in diametrically opposite positions. The tongues 22 can be replaced by an outer thread. A needle cap 24 engages with the needle-carrier 20 to cover the needle 2.

- 25 The plunger 4 can slide sealingly inside the chamber 10 of the syringe body 1. The plunger 4 is mounted on the head 40 of the shaft 41. The shaft 41 is cross-shaped in cross section and ends at the rear in a disc-shaped flange 42 which provides an abutment surface for the user's fingers during the injection.

- 30 Near the rear flange 42, around the shaft 41, an operating crown or disc 43 can be provided. A safety tongue 45 that protrudes radially and longitudinally outward from the shaft 41 is disposed between the rear flange 42 and the operating crown 43. The safety tab 45 is connected to the shaft 41 by means of a breakable connecting strip 46, such as a strip of perforated material acting as a line of weakening. In this manner the user can
35 remove the safety tongue 45 manually by tearing the line of weakening 46.

The operating crown 43 can be made in a single body with the shaft 41 or with the rear flange 42 of the shaft 41. In the case of the shaft 41 of the conventional syringe 100 not having the operating crown 43, said operating crown 43 can be made as a separate element forming part of the set of components 200 and thus able to be assembled to the shaft 41, as shown in the figures.

The set of components 200 comprises a sleeve 5, a spring 7, an abutment member 8 for the spring and optionally an operating crown 43.

As shown also in Figure 3, the abutment member 8 has a cylindrical or frusto-conical body 80 hollow on the inside, having an axial cavity 81 with a diameter substantially equal to the outside diameter of the front part of the syringe body 1 to be able to attached thereto by pressure. The abutment member 8 has at the front and axially a cylindrical or frusto-conical tang 82, with a smaller diameter than that of the body 80, so as to give rise to a shoulder 84. The tang 82 is hollow on the inside and has an inside thread 83.

In this manner, when the abutment member 8 is applied to the head of the syringe body, the tang 115 of the syringe body is disposed axially inside the tang 82 of the abutment member, leaving an annular space between the outer surface of the tang 115 of the syringe body and the inner surface of the tang 82 of the needle-carrier member, so as to give rise to a so-called Luer cone on the head of the syringe body to receive the needle-carrier 20 of the injection needle 2. In this case, the abutment member 8 acts as a supporting member for the needle 2.

As shown also in Figure 2, according to the invention, the set of components 200 comprises a safety device for the syringe, denoted by reference numeral 5 and taking the form of a substantially cylindrical sleeve, hollow on the inside, having an axial chamber open at the front and rear. The sleeve 5 has a front part 51 with a smaller diameter ending in an annular collar 52 that protrudes radially inward. The inside diameter of the body 50 of the sleeve body is slightly greater than the outside diameter of the body 80 of the abutment member 8, so that the sleeve 5 can slide axially on the body 80 of the abutment member 8, when the abutment member 8 is applied to the head of the syringe body 1.

Near the rear part of the body 50 of the sleeve there are provided two rigid tongues or flanges 53 which protrude radially outward, in diametrically opposite directions, to give rise to a resting surface for the user's fingers.

Two pairs of longitudinal flexible tongues 56, 66 are provided in the rear part of the body 50 of the sleeve, forward and rearward with respect to the flanges 53, respectively.

5 The first pair of tongues 56 is disposed forward of the flanges 53 and has two tongues 56 disposed in diametrically opposite positions. Each front tongue 56 is slightly inclined towards the inside and ends in a rear abutment surface 58. Each front tongue 56 is defined by a substantially U-shaped cut 57 made on the body of the sleeve, so as to be able to bend with respect to the sleeve body.

10

The second pair of tongues 66 is disposed to the rear of the flanges 53 and has two tongues 66 disposed in diametrically opposite positions. Each rear tongue 66 is inclined slightly inward and ends in a front abutment surface 68, substantially opposed to the rear abutment surface 58 of the respective front tongue 56. Each rear tongue 66 is defined by
15 a substantially U-shaped cut 67 made in the body of the sleeve, so as to be able to bend with respect to the body of the sleeve.

20

Lastly, the set of components 200 comprises the spiral spring 7, designed to be housed in the front part 52 of the sleeve body. In fact the outside diameter of the spring 7 is slightly smaller than the inside diameter of the front part 51 of the sleeve body 5.

Assembly of the set of components 200 on the syringe 100 will be described hereunder, purely by way of example, with the aid also of Figure 4.

25 The guard mechanism 200 can be supplied pre-assembled. That is to say, the spring 7 is inserted in the sleeve 5, from the rear of the sleeve 5, so that the end of the spring abuts against the collar 52 of the front part of the sleeve 5. The abutment member 8 for the spring is then inserted into the sleeve, again from the rear of the sleeve, so that the shoulder 84 of the abutment member abuts against the other end of the spring. Then, by
30 lightly forcing the abutment member 8 into the sleeve, the body 80 of the abutment member passes the pair of rear tongues 66 and thus the rear edge of the abutment member is blocked by the front abutment surface 68 of the rear tongues of the sleeve, preventing the abutment member from coming out of the sleeve.

35 At this point the pre-assembled protection mechanism 200 can be attached to a conventional syringe 100, mechanically or manually. In fact, it is sufficient to force the

syringe body 1 into the sleeve 5, from the rear of the sleeve. In this manner the tang 115 of the syringe body is inserted into the abutment member 8 until the shoulder 15 of the syringe body 1 abuts against the shoulder 84 of the abutment member. In this situation the abutment member 8 is integral with the front part of the syringe body 1 and a Luer cone consisting of the inside tang 115 of the syringe body and the outside tang 82 of the abutment member is formed in the head of the syringe body. By advancing the syringe body and causing the tongues 56 to bend slightly outwards, possibly with the aid of suitable means, the syringe body pushes the abutment member 8 slightly forward, compressing the spring in the front part 51 of the sleeve.

10

As shown in Figure 4, when the rear edge 11 of the syringe body passes the pair of rear tongues 66 of the sleeve, the front abutment surface 68 of the rear tongues 66 abuts against the rear edge 11 of the syringe body, preventing the syringe body from coming out of the sleeve 5 through the action of the spring 7. At this point the syringe 100 with the guard mechanism 200 is ready for use.

15

It should be noted that in this situation the safety tab 45 fixed to the shaft 41 abuts against the rear edge of the sleeve 5, preventing the shaft 41 from advancing further, so that the operating crown 43 does not cooperate with the rear tongues 66 of the sleeve, triggering the guard mechanism 200.

20

Operation of the syringe 100 provided with the guard mechanism 200 according to the invention is described hereunder with reference to Figures 5 to 8.

Before carrying out the injection, the user manually tears the safety tab 45 along the perforated line of weakening 46.

25

As shown in Figure 5, when the plunger 4 reaches the end of its injection stroke inside the chamber of the syringe body, the operating crown 43 of the shaft 41 comes into contact with the flexible rear tongues 66 of the sleeve, causing outward bending of said tongues 66.

30

As a result, the rear edge 11 of the syringe body disengages from the protrusions 68 of the rear tongues 66. Consequently, axial movement of the sleeve 5 with respect to the syringe body 1 is no longer prevented. Thus through the action of the spring 7 which is released, the sleeve 5 can move axially forward with respect to the syringe body 1 and/or

35

the syringe body 1 can move axially rearward with respect to the sleeve 5. It should be noted movement of the sleeve 5 takes place automatically through the action of the spring 7 without the need for any manual intervention by the user.

- 5 As shown in Figure 7, said telescopic movement of the sleeve 5 and of the syringe 100 is controlled and regulated by the user's hand. In fact the user keeps the index and middle finger on the flanges 53 of the sleeve and the thumb on the rear flange 42 of the plunger shaft, accompanying the stroke of the sleeve 5 and of the syringe 100 towards the position of safety and thus regulating the speed of relative movement of the sleeve 5 with
10 respect to the syringe 1 as desired by the user.

- At the end of the stroke of the sleeve 5, as shown in Figures 6 and 8, the body 80 of the abutment member 8 is retained between the two pairs of tongues 56 and 66. That is to say, the rear abutment surface 58 of the front tongues 56 abuts against the shoulder 84 of
15 the abutment member, preventing forward movement thereof, whilst the front abutment surface 68 of the rear tongues 66 abuts against the rear edge of the body 80 of the abutment member, preventing rearward movement thereof. Detachment of the abutment member 8 from the syringe body can be caused by exerting a strong forward traction on the sleeve, but the needle 2 nevertheless remains trapped, together with the abutment
20 member, in the sleeve 5.

It should be noted that in the present invention, the spring 7 remains protected inside the sleeve 5, even when the sleeve 5 is in its forward safety position.

- 25 It should further be noted that in the present invention, a syringe of a conventional type, composed of the body 1, the plunger 4 with the shaft 41 thereof and the needle 2 with the support 20 thereof, is made into a safety syringe by the use of only three additional elements forming part of the guard mechanism 200, that is to say, the sleeve 5, the spring 7 and the abutment member 8. Furthermore, the set of components 200 can optionally
30 also comprise the operating crown 43 to be applied to the shaft 41 of the piston, in the event of said operating crown 43 not being made integral or in a single body with the shaft 41.

- Numerous variations or modifications of detail within the reach of a person skilled in the
35 art can be made to the present embodiment of the invention, without thereby departing from the scope of the invention as set forth in the appended claims.

CLAIMS

1. A guard mechanism (200) attachable to a syringe (100) to make it into a disposable automatic safety syringe, said syringe (100) comprising:
- a syringe body (1) hollow on the inside and open at the front and rear,
 - a plunger (4) sliding inside the syringe body (1) with an injection stroke extending from a retracted syringe-filling position to a forward syringe-emptying position, said plunger (4) being provided at the rear with a shaft (41) that can be operated manually and brought out of the syringe body by means of the rear end (42) thereof, and
 - an injection needle (2) incorporated into a needle-carrier (20) engageable in the head (115) of the syringe body (1),
- characterised in that said guard mechanism (200) can be pre-assembled and comprises:
- a sleeve (5) that can be slidably mounted on said syringe body (1),
 - a spring (7) housed in said sleeve (5),
 - a abutment member (8) for said spring (7), also housed in said sleeve (5) and able to be made integral with the front part of said syringe body (1).
2. A mechanism (200) according to claim 1, characterised in that in said pre-assembled condition, said abutment member (8) for said spring (7) is retained by locking means (66) in the form of flexible tongues protruding inward from said sleeve (5).
3. A mechanism (200) according to claims 1 and 2, characterised in that in during operation said sleeve (5) is slidably mounted on said syringe body (1), to pass from a retracted position of use of the syringe, to a forward position of safety, wherein it covers said needle (2), and said spring (7) is disposed under compression in the front part of said sleeve (5), between said sleeve (5) and said abutment member (8) made integral with said syringe body (1), to urge the axial movement of the sleeve (5) with respect to the syringe body, there also being provided:
- locking means (66, 11) disposed in the rear part of the sleeve (5) and in the rear part of the syringe body (1), in reciprocal engagement, to keep the sleeve locked in the retracted position of use against the action of said spring (7), and
 - operating means (43) disposed in said shaft (41) to release said locking means (56), when the plunger (4) reaches the end of the injection stroke, so as to allow the axial movement of the sleeve into the safety position, thanks to the action of said spring (7).

4. A mechanism (200) according to any one of the preceding claims, characterised in that said abutment member (8) comprises:

- a cylindrical or frusto-conical body (80), hollow on the inside to be applied to the front part of the syringe body (1), e
- 5 - a cylindrical or frusto-conical tang (82) with a smaller diameter than the body (80) and protruding forward therefrom so as to give rise to a shoulder (84).

10 5. A mechanism according to claim 4, characterised in that said spring is a spiral spring (7) disposed in the front part (51) of the sleeve, around the tang (82) of the abutment member, with one end of the spring (7) abutting against a collar (52) protruding inward in the front edge of the front part (51) of the sleeve and the other end of the spring abutting against the shoulder (84) of the abutment member.

15 6. A mechanism (200) according to any one of the preceding claims, characterised in that formed in said sleeve (5) are locking means (56, 66) cooperating with said abutment member (8) to lock the sleeve when it is in its forward position of safety.

20 7. A mechanism (200) according to claim 6, characterised in that said locking means (56, 66) to lock the sleeve (5) in the forward position of safety comprise a pair of front tongues (56) opposed to a pair of rear tongues (66) formed in said sleeve (5), said pair of front tongues (56) having rear abutment surfaces (58) able to abut against the shoulder (84) of the abutment member (8) and said pair of rear tongues (66) having front abutment surfaces (68) to abut against the rear edge of the body (80) of the abutment member.

25 8. A mechanism according to claim 7, characterised in that said pairs of opposed tongues (56, 66) of the sleeve are flexible and are formed by means of substantially U-shaped opposed cuts (57, 67) in the sleeve body, to be able to bend radially inward and outward with respect to the sleeve.

30 9. A mechanism according to any one of the preceding claims, characterised in that said locking means for locking the sleeve (5) in the retracted position of use comprise a collar (11) protruding radially outward from the rear edge of the syringe body (1) able to abut against said flexible rear tongues (66) formed in the rear part of the sleeve (5), said flexible tongues (66) ending in respective abutment surfaces (68) able to abut against
35 said collar (11) to retain the syringe body.

10. A mechanism according to claim 9, characterised in that said flexible tongues (66) are inclined slightly inward to cooperate with said circular operating crown (43), when the plunger is at the end of the injection stroke.

5 11. A mechanism according to any one of the preceding claims, characterised in that said sleeve (5) has outwardly protruding gripping means (53), to give rise to a resting surface for the user's fingers.

12. A disposable automatic safety syringe (100) comprising:

- 10 - a syringe body (1) hollow on the inside and open at the front and rear,
- a plunger (4) sliding in the syringe body (1) with an injection stroke extending from a retracted syringe-filling position to a forward syringe-emptying position, said plunger (4) being provided at the rear with a shaft (41) that can be operated manually and brought out of the syringe body by means of the rear end (42) thereof,
15 - an injection needle (2) supported by a needle-carrier (20) engageable to the front end (13) of the syringe body (1),
- a sleeve (5) slidably mounted over said syringe body (1), to pass from a retracted position of use of the syringe wherein the needle protrudes forward therefrom, to a forward position of safety, wherein it covers said needle (2),
20 characterised in that it further comprises:
- a abutment member (8) able to be made integral with the front part of the syringe body (1),
- spring means (7) disposed under compression in the front part of said sleeve (5), between said sleeve (5) and said abutment member (7) to urge the axial movement of the
25 sleeve (5) with respect to the syringe body,
there further being provided:
- locking means (66, 11) provided in the rear part of the sleeve (5) and in the rear part of the syringe body (1), in reciprocal engagement, to keep the sleeve locked in the retracted position of use against the action of said spring means (7), and
30 - operating means (43) disposed in said shaft (41) to disengage said locking means (66), when the plunger (4) reaches the end of the injection stroke, so as allow axial movement of the sleeve into the safety position, thanks to the action of said spring means (7).

13. A syringe (100) according to claim 12, characterised in that said abutment member
35 (8) comprises:

- a cylindrical or frusto-conical body (80), hollow on the inside to be applied to the front part of the syringe body (1), and
- a cylindrical or frusto-conical tang (82) with a smaller diameter than that of the body (80) and protruding forward therefrom so as to give rise to a shoulder (84).

5

14. A syringe according to claim 13, characterised in that said spring means comprise a spiral spring (7) disposed inside the front part (51) of the sleeve, around the tang (82) of the abutment member, with one end of the spring abutting against a collar (52) protruding inward in the front edge of the front part (51) of the sleeve and the other end

10

15. A syringe according to any of claims 12 to 14, characterised in that in said sleeve (5) there are formed locking means (56, 66) cooperating with said abutment member (8) to lock the sleeve when it is in its forward position of safety, said locking means (56, 66) comprising a pair of front tongues (56) opposed to a pair of rear tongues (66) formed in said sleeve (5), said pairs of front tongues (56) having rear abutment surfaces (68) able to abut against said shoulder (84) of the abutment member (8) and said pair of rear tongues (66) having front abutment surfaces (68) able to abut against the rear edge of the body (80) of the abutment member (8).

20

16. A syringe according to claim 15, characterised in that said locking means for locking the sleeve (5) in the retracted position of use comprise a collar (11) protruding radially outward from the rear edge of the syringe body (1) and able to abut against the pair of flexible rear tongues (66) formed in the rear part of the sleeve (5).


25

17. A syringe according to any one of claims 12 to 16, characterised in that in the rear part of said shaft (41) of the plunger (4) there is provided a safety tab removable by the user and able to abut against the rear edge of the sleeve (5) to prevent the plunger from reaching the end of the injection stroke.

30

18. A syringe according to any one of claims 13 to 17, characterised in that said tang (82) of the contrast element (8) is shaped on the inside as a Luer cone to support the needle-carrier (20).

35






FIG. 2




FIG. 4




FIG. 5






FIG. 6

4/4



INTERNATIONAL SEARCH REPORT

In International Application No
PCT/IT 02/00730

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61M5/32 A61M5/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 376 080 A (PETRUSSA GIAN L) 27 December 1994 (1994-12-27) column 3, line 51 -column 4, line 56; figures 1-5	1,3-5, 9-14,17 18
Y	column 6, line 23 - line 41; figures 10-13	
X	WO 01 85239 A (SAFETY SYRINGES INC) 15 November 2001 (2001-11-15) page 19, line 1 -page 24, line 10; figures 7-11,16	1-3,11
X	US 5 267 976 A (POIRIER DOMINIQUE ET AL) 7 December 1993 (1993-12-07) column 3, line 14 -column 4, line 18; figures 1-3	1,3-6, 11-14
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

24 April 2003

Date of mailing of the international search report

09/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Björklund, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 02/00730

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 37345 A (RIGHI NARDINO ;ROSSI ROBERTO (IT); RESTELLI SERGIO (IT)) 29 July 1999 (1999-07-29) cited in the application	1
Y	figures 1,4	18
X	US 6 206 853 B1 (BONNET JEAN-PIERRE) 27 March 2001 (2001-03-27) figures 1-6	1,3-5, 9-14
X	US 5 273 541 A (MALENCHEK ROBERT) 28 December 1993 (1993-12-28) column 3, line 13 -column 4, line 50; figures 1-6	1,3-5, 9-14
A	US 5 433 712 A (SHERWIN DEWAYNE J ET AL) 18 July 1995 (1995-07-18) figures 1-8	1-18
A	US 5 843 041 A (FLODMAN MICHAEL R ET AL) 1 December 1998 (1998-12-01) column 6, line 11 - line 26; figure 2	1,12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT 02/00730

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5376080	A	27-12-1994	IT 1248125 B AT 137122 T DE 69210060 D1 DE 69210060 T2 EP 0497220 A1	05-01-1995 15-05-1996 30-05-1996 24-10-1996 05-08-1992
WO 0185239	A	15-11-2001	EP 1284769 A2 WO 0185239 A2	26-02-2003 15-11-2001
US 5267976	A	07-12-1993	FR 2650187 A2 AT 112690 T DE 69013363 D1 DK 519922 T3 EP 0519922 A1 ES 2074168 T3 WO 9113643 A1	01-02-1991 15-10-1994 17-11-1994 18-04-1995 30-12-1992 01-09-1995 19-09-1991
WO 9937345	A	29-07-1999	IT SV980003 A1 AU 741678 B2 AU 2517899 A BR 9907718 A CA 2318594 A1 CN 1288391 T WO 9937345 A1 EP 1049503 A1 JP 2002500934 T US 6419658 B1	20-07-1999 06-12-2001 09-08-1999 18-12-2001 29-07-1999 21-03-2001 29-07-1999 08-11-2000 15-01-2002 16-07-2002
US 6206853	B1	27-03-2001	FR 2764195 A1 AT 229826 T AU 7924998 A DE 69810291 D1 EP 0988076 A1 WO 9856442 A1 JP 2002503127 T	11-12-1998 15-01-2003 30-12-1998 30-01-2003 29-03-2000 17-12-1998 29-01-2002
US 5273541	A	28-12-1993	NONE	
US 5433712	A	18-07-1995	NONE	
US 5843041	A	01-12-1998	US 5314414 A US 5256153 A US 5019051 A WO 9428954 A1 AT 163360 T BR 9206037 A CA 2109713 A1 DE 69224521 D1 DE 69224521 T2 EP 0585391 A1 JP 6507804 T MX 9202429 A1 WO 9220390 A1 US 6017329 A CA 2009560 A1 US 5141500 A	24-05-1994 26-10-1993 28-05-1991 22-12-1994 15-03-1998 02-08-1994 26-11-1992 02-04-1998 18-06-1998 09-03-1994 08-09-1994 01-11-1992 26-11-1992 25-01-2000 02-09-1990 25-08-1992